

## CUTTING CONDITIONS

## Drilling | Indexables | Cutting conditions

# PHP

Work Material		Tensile Strength/ Hardness	Drilling speed Vc (m/min)	Feed Rate (mm/rev)			
				ø14~ø20.5	ø21~ø28	ø29~ø34	ø35~ø40
P	Mild Steel-Carbon Steel (S5400-S10C)	~180HB	200 (150 ~ 250)	0,09 (0,06 ~ 0,13)	0,13 (0,10 ~ 0,18)	0,18 (0,13 ~ 0,21)	0,25 (0,20 ~ 0,27)
	Carbon Steel-Alloy Steel (S50C-SCM440)	~280HB	160 (100 ~ 220)	0,09(0,06 ~ 0,13)	0,13 (0,10 ~ 0,18)	0,18 (0,13 ~ 0,21)	0,25 (0,20 ~ 0,27)
	Die steel (SKD11-SKD61)	~280HB	140 (80 ~ 180)	0,08 (0,05 ~ 0,12)	0,12 (0,06 ~ 0,15)	0,14 (0,09 ~ 0,18)	0,15 (0,10 ~ 0,20)
M	Stainless Steel (Dry) (SUS304-SUS420)	~250HB	150 (100 ~ 180)	0,08 (0,05 ~ 0,12)	0,10 (0,06 ~ 0,12)	0,15 (0,10 ~ 0,17)	0,18 (0,15 ~ 0,20)
K	Cast Iron (FC250)	~350N/mm²	150 (100 ~ 180)	0,09 (0,06 ~ 0,13)	0,13 (0,10 ~ 0,18)	0,18 (0,13 ~ 0,21)	0,25 (0,20 ~ 0,27)
	Ductile Cast Iron (FCD400)	~800N/mm²	130 (80 ~ 150)	0,09 (0,06 ~ 0,13)	0,12 (0,08 ~ 0,16)	0,16 (0,1 ~ 0,20)	0,20 (0,15 ~ 0,25)
N	Alluminium Alloy	~13%Si	220 ( 100 ~ 800)	0,09 (0,06 ~ 0,20)	0,13 (0,10 ~ 0,25)	0,18 (0,13 ~ 0,30)	0,25 (0,20 ~ 0,35)
S	Heat Resistant Aluminium Alloy(Wet) (Inconel 718)	—	30 (15 ~ 50)	0,04 (0,02 ~ 0,06)	0,06 (0,03 ~ 0,10)	0,08 (0,04 ~ 0,12)	0,10 (0,06 ~ 0,14)
	Titanium Alloy (Wet) (Ti-6Al-4V)	—	60 (30 ~ 100)	0,06 (0,04 ~ 0,08)	0,08 (0,06 ~ 0,12)	0,10 (0,08 ~ 0,15)	0,12 (0,10 ~ 0,15)

1. The indicated speeds and feeds are for water soluble oil.
2. Suitable cutting fluid is water soluble high density oil (less than 20 times dilution).
3. Using non-water soluble oil is not recommended.
4. These conditions are for drilling depth less than 3 times the drill diameter.
5. Inserts should be attached to the holder tightly in a very neat condition.
6. Fasten the work material to reduce the possibility of work deformation, deflection of machined surface, or vibration.
7. A clogged oil hole can lead to a breakage. Make sure that a filter is attached to the oil feeder.